

TECHNICAL DATA SHEET

INTRODUCTION :

NV-202 is a high grade of heat cracked PE wax ,made from brand new PE resin ,high dispersancy ,high whiteness ,suitable to use in most kinds of plastic processing ,specially recommended in high filler masterbatch .

PROPERTIES	PE WAX NV-202		
	UNIT	DATA	TEST METHOD
Appearance/外观	WHITHE POWDER		
Viscosity(@140°C)/粘度	CPS	400±50	BROOKFIELD
Softening Point/软化点	°C	110±5	ASTM
Density/密度	g/cm ³	0.93	ASTM
Penetration(@25°C)/针入度	d-mm	2	ASTM
TG/热失重	%	1	CONSTANT TEMPERATURE
Particle Size/粒径	%	99	20 MESH THROUGH

APPLICATION:

NOVO® POLYETHYLENE WAX	202	201	201H	208
Masterbatch/色母粒	*	*	*	**
Filler Masterbatch/填充母料	**	**	**	**
PVC	**	**	**	*
Cable Filler/电缆填充	*	*	*	*
Hot Melt Adhesive/热熔胶	**	**	**	*
Thermoplastic Road Marking/热塑性路标	**	**	**	**
Candle/蜡烛	**	**	**	**
Rubber/橡胶	*	*	*	**

* suitable

** recommend

PACKAGE: 25KG/BAG

SAFETY INSTRUCTIONS: Please refer to SDS for more information

For more information ,please visit : www.chemnovo.com.cn